

### SAFETYDATA SHEET

## Section 1 - Product and Identification

Product Name: WoodProTech<sup>TM</sup> Wood Treated Article

Synonyms: None CAS. NO.: None

Description: Treated Solid Wood/Panels and Engineered Wood Products.

Wood Product Identifier: Fire Retardant - Preservative Treated Wood

Finished Product Identifier: Red colorant on all six sides of the treated wood (various colors)

Manufacturer: Wood Protection Technologies, Inc.

11568 Sorrento Valley Rd. Ste. 13

San Diego, CA. 92121 1-858-780-4747

Date of Revision: 07/06/2018 (Revision E)

## Section 2 - Hazard Identification

**OHSA/HCS status**: This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### Classification of the Substance or Mixture:

Acute Toxicity (inhalation) - Category 4
Acute Toxicity Oral - Category 4
Skin Corrosion/Irritation - Category 4
Serious Eye Damage - Category 4
Skin sensitization - Category 3

Specific Target Organ Toxicity- single exposure - Category 4

#### **GHS Label Elements**

Signal Word: WARNING



#### **Hazard Statement:**

May cause an allergic skin reaction May cause respiratory irritation

#### **Precautionary Statements:**

Wear personal protective equipment.

Wear protective gloves.

Wash skin thoroughly after handling

Do not eat drink or smoke when using this product

Contaminated work clothing should not be allowed out of the workplace

### **Response:**

**IF SWALLOWED:** This product is not expected to be ingested. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Stop if the exposed person feels

sick as vomiting may be dangerous.

**IF ON SKIN:** Wash skin with soap and water. Prolonged or repeated skin contact may cause allergic

reaction in some people. If continued reaction, please call Poison Center or Doctor for

Treatment advice.

**IF INHALED:** This product is not expected to be toxic by inhalation. Use normal wood handling

precautions and wood dust warnings.

**IF IN EYES:** This product is not expected to be an eye irritant.

**STORAGE**: Treated wood should be stored under cover at least 6 inches from the ground. Avoid

constant wetting or other direct sources of moisture.

**DISPOSAL**: Dispose in a sanitary landfill, or by procedure approved by local and state authorities.

#### Hazards Not Otherwise Classified: None known

# Section 3 - Hazardous Components

Chemical Ingredients	SARA-313	CAS #	
Water:	-	7732-18-5	
WoodSurfaceFilm <sup>TM</sup> Concentrate Re-	v E(a):	Proprietary	
AF21/FRC12 Fire Inhibitor:	-	Proprietary	
Disodium Octaborate Tetrahydrate .4	2pcf (~15%) -	64405-8	
Pigment	-	Proprietary	

**Note:** Above levels are below report ability requirements determined by the OSHA Hazard Communication Standards (HCS)

# Section 4 - First Aid Measures

### Description of first aid measures

**Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Call 911 or medical services, then apply artificial respiration.

**Skin contact:** Wash skin with soap and water. Prolonged or repeated skin contact may cause allergic reaction in some people. If continued reaction, please call Poison Center or Doctor for Treatment advice.

**Eye contact:** This product is not expected to be an eye irritant. If accident occurs, immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. If continued or chronic pain, please call Poison Center or Doctor for treatment advice.

**Ingestion:** This product is not expected to be ingested. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous.

Aside from the information found under description of first aid measures (above), additional important symptoms and effects are described in Section 11: Toxicology Information.

## Section 5 - Fire

Flash Point: Not Applicable
Flammable Limits: Not applicable
Explosive Limits in Air: <40 grams M3 (LEL)

Extinguishing Media: Use water spray, dry chemicals, or carbon dioxide.

Fire Fighting Instructions: Use self-contained breathing apparatus and protection for skin. Wet down with

water. Wet down dust to reduce dispersion of dust into the air. Remove burned or

wet dust to open area.

Special Hazards: Not applicable

## Section 6 - Accidental Release Measures

Not Applicable

Special Hazards: Not applicable

# Section 7 - Handling and Storage

Precautions Taken in Handling and Storage:

Use standard wood handling procedures. Treated wood products should be stored a minimum of 6 inches from ground contact and properly wrapped per OEM specifications. Avoid constant wetting or other direct sources of moisture. Please refer to Quality Control Manual for further precautions.

# Section 8 - Exposure Controls / Personal Protection

### Personal Protective Equipment (PPE)

Respiratory Protection: None required in well-ventilated areas. An approved organic vapor full-face

respirator is advised for poorly ventilated areas.

Ventilation; Local Exhaust: None required.

Mechanical (General): Provide adequate ventilation.

Protective Gloves: Not required.

Eye Protection: Wear approved safety glasses with side shields.

Other Protective Equipment: Wear protective work clothing. Launder contaminated clothing before reuse.

### **Exposure Limit- Wood Dust**

\*\*\*\*WARNING\*\*\*\* Drilling, sawing, sanding or machining wood products generates wood dust, a

substance known to the State of California to cause cancer. Avoid inhaling wood

dust or use a dust mask or other safeguards for personal protection.

ACGIH TLV(A): TWA-50 mg/m<sub>3</sub> STEL (15min.)-10 mg/m<sub>3</sub> Softwood

TWA -1.0 mg/m<sub>3</sub>: Certain hardwoods such as beech and oak

OSHA PEL: OSHA's Air Contaminants Rule, including OSHA's wood dust PEL's was struck

down in AFL-CIO v. OSHA, 985F.2d 952 (11th CIR. 1992), a number of states have incorporated those provisions in their state plans. Additionally, OSHA has announced that it may cite companies under the OSH Act general duty clause under

appropriate circumstances for non-compliance with those levels.

TWA-50 mg/m<sub>3</sub> STEL (15min.) -10 mg/m<sub>3</sub> Softwood All softwoods, hard woods, except Western Red Cedar.

Western Red Cedar: TWA-2.5 mg/m

## Section 9 - Physical and Chemical Properties

Physical Appearance: Light Red Color on surface of substrate.

Odor: Dependent on wood species

pH @ 22\*C: Not Applicable
Boiling Point: Not Applicable
Melting Point: Not Applicable
Solubility in Water: Insoluble

Evaporation Rate: Not Applicable Butyl Acetate = 1: Not Applicable

Specific Gravity: Depends on wood species and moisture content.

## Section 10 - Stability and Reactivity

Reactivity: no data available

Chemical stability: no data available

Possibility of hazardous reactions: Stable under recommended storage conditions. Product will not undergo

Hazardous Polymerization.

Conditions to avoid: no data available

If this product becomes a waste, it does not exhibit the properties of ignitability, corrosivity, reactivity, or environmentally persistent toxicity. The material should not be flushed into any sewer system.

## Section 11 - Toxicological Information

LD<sub>50</sub>: Not determined. Similar products tested for LD<sub>50</sub>limit value are greater than 10,000

mg / KG.

Threshold Limit Value: No limit determined.

Effects of Acute Exposure

Ingestion: Nausea may occur.

Inhalation: Prolonged exposure may produce headaches, and mucous membrane irritation.

Skin Contact: Direct contact will not cause irritation. Eye Contact: Direct contact will not cause irritation.

Effects of Chronic Exposure: None determined

## Section 12 - Ecological Information

This product contains Disodium Octaborate Tetrahydrate, Boron (B) is an element which occurs naturally in seawater at an average concentration of 5 mg B/L and generally, occurs in freshwater at concentrations up to 1 mg B/L. To convert Disodium Octaborate Tetrahydrate into equivalent boron (B) content, multiply by 0.2096. Boron is an essential micronutrient for healthy growth of plants; however, it can be harmful to boron sensitive plants in high quantities. Care should be taken to minimize the amount of the product released to the environment.

## Section 13 - Disposal Considerations

### **Recommended Waste Disposal Methods:**

Material should not be flushed into any sewer system. This product and any residual material left in its packaging may be incinerated, or absorbed with an inert absorbent material and land filled. After the material has been collected, dispose of in accordance with all local and national regulations applicable to non-hazardous liquid

wastes. Dispose in a sanitary landfill, or by procedure approved by local and state authorities. Wood scrapes can be ground up for use as mulch in gardens. Disodium Octaborate Tetrahydrate is not listed under any sections of the Federal Resource Conservation and Recovery Act (RCRA).

# Section 14 - Transport Information

This product is classified as "Non-flammable, Non-hazardous, Not Restricted" for Transport purposes.

United Nations Number: None.
ADR/RID Class: IATA Class: IMO Class: IMDG Code: -

Marine Pollutant Classification: - Not classified as a Marine Pollutant.

Shipping Description	Bulk Shipments	Non-bulk Shipments
Proper Shipping Name:	Non-regulated	Non-regulated
Hazard Class:	Not applicable	Not applicable
Identification No.:	Not applicable	Not applicable
Packing Group:	Not applicable	Not applicable
Reportable Quantities:	Not applicable	Not applicable
Placards / Labels:	Not applicable	Not applicable
Special Provisions		
for Transport:	Not applicable	Not applicable

## Section 15 - Regulatory Information

### **OSHA Hazard Communication Standard**

This product is not classified as dangerous for the User under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### California (Proposition 65): In Compliance.

None of the components of this product are on the proposition 65 list published as of April 22, 2016.

AICS: (Australia) Not determined.

EINECS: (Europe) This product meets the definition of a polymer under the 7th Amendment to

Directive 67/548/EEC. (92/32/EEC).

CEPA DSL: (Canada) Not determined

Handbook of Existing and New Chemical Substances

(Japan): Not determined.

Toxic substances

Control Act: (USA) This product is on the 8(B) Inventory List (40 CFR 710).

SARA: (USA)

Section 302- This product does not contain materials listed in Appendix A or B as an Extremely

Hazardous Substance.

Sections 311/312- Materials listed in 29 CFR 1910, Subpart Z are identified in Section III. None is

known or suspected carcinogens listed by the National Toxicology Program,

International Agency for Research on Cancer, or OSHA.

Section 313- Listed materials contained in this product are identified in Sections II and II of this

MSDS.

Clean Air Act: (USA)

This product does not contain, and has not contacted during manufacture, any

Ozone Depleting Substances.

Food Packing Use: This product is for Industrial Use only. It is not approved for any applications

involving food packaging or contact.

### Section 16 – Other Information

**Federal Regulations** 

CERCLA / SARA: Spills or releases of this material do not currently trigger emergency release

reporting requirements under CERCLA or SARA Title III. State or local reporting requirements may differ from federal requirements. Consult counsel for further

guidance on your responsibilities under these laws.

Other Regulations: Not applicable


Classification: Not classified as dangerous for the User.

Risk Phrases: Warning Signs:

Countries outside the EEC: WHMIS Classification – Class D, Division 2.

Hazard Rating Information Table: 0 = Insignificant 3 = Serious 1 = Slight 4 = Severe

2 = Moderate



This product must be used in accordance with released manufacturing and quality control documentation as supplied by Wood Protection Technologies, Inc. The Company cannot anticipate all of the handling and use of this product. Therefore, Wood Protection Technologies, Inc. accepts no responsibility for results obtained by the application of this product, use of this information or the safety and suitability of our products either alone or in combination with other products outside the scope of our published documentation or product labeling. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. Wood Protection Technologies, Inc. will not accept any liability for damages or loss incurred from the improper handling and use of this product.

WoodProTech<sup>tm</sup> Protected Lumber is a registered trademark of Wood Protection Technologies, Inc. WoodSurfaceFilm<sup>tm</sup> is a registered trademark of Eco Building Products, Inc.

For further information, contact: Wood Protection Technologies, In.

Technical and Sales Support: 858-780-4747